



Declaration of Performance

According to annex III of the regulation (EU) Nr. 305/2011

For the product-type Chipboard screws

Nr. DOP-AT-19-05-15

1. Unique Identification code of product-type

Item Number: see product packaging

2. Type-, Batch-, or Serial Number or any other element identification of the construction product as required pursuant to Article 11 Paragraph 4:

Batch Number: see product packaging

3. Intended use or uses of construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For timber structure load

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 Paragraph 5:

Conmetall Meister GmbH

Oberkamper Str. 37-39

42349 Wuppertal / Germany

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 Paragraph 2:

Not relevant

6. System or Systems of assessment and verification of performance of the construction product as set out in Annex V:

System 3

7. In case of the Declaration of Performance concerning a construction product covered by a harmonized standard:

EN14592:2008+A1:2012, System 3:

Notified Body No.: 1015

13.06.2019

8. In case of the Declaration of Performance concerning a construction product for which an European Technical Assessment has been issued:

Not relevant

9. Declared Performance

To which this declaration relates is in conformity with

System 3 of (EU) No. 305/2011 and EN 14592:2008+A1:2012

and are tested by

STROJÍRENSKÝ ZKUŠEBNÍ ÚSTAV, s. p. (Notified Body No. 1015)

The reference test report no.

ψ 3.0mm / No. 1015-CPR-30-10782/1

ψ 3.5mm / No. 1015-CPR-30-10782/2

ψ 4.0mm / No. 1015-CPR-30-10782/3

ψ 4.5mm / No. 1015-CPR-30-10782/4

ψ 5.0mm / No. 1015-CPR-30-10782/5

ψ 6.0mm / No. 1015-CPR-30-10782/6

Essential characteristics	Performance	Harmonised technical specification
Mechanical resistance and stability	Reference to Annex 1	EN 14592:2008+A1:2012
Safety in case of fire	A1	EN 13501-1:2007+A1:2009
Hygiene, health and the environment	NPD	-
Safety and accessibility in use	NPD	-
Protection against noise	NPD	-
Energy economy and heat retention	NPD	-
Sustainable use of natural resources	NPD	-

ANNEX I Product identification and the initial-type testing findings

Table 1:

Product	Length	Characteristic yield moment $M_{0,2}$ [Nm/mm]		characteristic withdrawal parameter $f_{0,2}$ [N/mm ²]		Characteristic head pull-through parameter $f_{0,2,2}$ [N/mm ²]	Characteristic tensile capacity $f_{0,2,1}$ [kN]	Characteristic torsional ratio
				Loading across the fibre	Loading along the fibre			
Screw Ø 3.0 mm	12-40 mm	1 896		19,86	14,13	25,79 ^{nat csk} 30,96 ^{pan}	3,72	1,86
Screw Ø 3.5 mm	14-50 mm	2 931		19,30	13,77	25,60 ^{nat csk} 31,02 ^{pan}	5,28	1,98
Screw Ø 4.0 mm	16-70 mm	3,358		17,53	13,78	24,23 ^{nat csk} 29,75 ^{pan}	5,79	2,40
Screw Ø 4.5 mm	18-80 mm	Thread section	smooth section	19,72	13,99	23,00 ^{nat csk} 27,58 ^{pan}	7,88	2,95
		5 294	11 548					
Screw Ø 5.0 mm	40-120 mm	6,575		19,70	15,15	21,84 ^{nat csk} 25,07 ^{pan}	9,20	3,12
Screw Ø 6.0 mm	40-240 mm	11 930		18,76	15,27	21,08 ^{nat csk} 25,26 ^{pan}	14,01	2,64
Material	Carbon Steel C1018/C1022							
Corrosion resistance	Yellow Zinc Plated / Zinc plated (service class 1 acc. to EN 1995-1-1)							

10. The Performance of the Product identified in points 1 and 2 is in conformity with the declared performance in point 9. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in Point 4:

Signed for and on behalf of the manufacturer by:

(Date)

(Signature)

ppa. Cornelia Koch
Leitung Qualitätsmanagement
Head of Quality Management

Conmetall Meister GmbH
Oberkamper Straße 37-39
42349 Wuppertal
- Zweigstelle -

I. A. Julian Sarrazin
Einkauf Eisenwaren Discount
Purchasing Manager
Ironmongery
Discount

13.06.19

